

DP703A

7" POS Display



FENGYU



Main Features

- 7" screen, sealed zero-bezel design with tamper proof glass
- Step edge design with VESA mounting hole on the back cover
- SVGA (800 x 480) resolution
- Available in USB, VGA and HDMI interfaces
- USB interface, powered by USB interface
- With optional PCAP touch
- Available with two stands: Standard Stand and Long Pole Stand

Technical Specification



[Panel Spec]	
TFT Panel Resolution	7" · 800 x 480 (ratio 5:3)
Active Area	154.08 x 85.92 mm
Contrast Ratio	800:1
Luminance	400cd/m ²
Response Time	25ms
Viewing Angle	60°/ 70°/ 80°/ 80° (Up/ Down/ Left/ Right)
Touch Panel	PCAP multiple touch (10 points), optional
[Electrical]	
[USB interface]	
Power Input	USB 5V
Current	0.5A
Driver	DisplayLink
Cable Length	1.8m (USB-C to USB-A 2.0)
[Others]	
Storage Temperature	-20°C ~ 70°C
Operating Temperature	0°C ~ 60°C
Operating Humidity	10% ~ 80%
Mounting	VESA compliant (75mm x 75mm)
Stands	DZ-001 / DZ-002 / DZ-003 / DZ-007/ Standard and Long pole stand
Dimensions (Panel bezel)	182 x 120 x 27, mm