

K104I-S



HENGYU



K104I-S



Main Features

Professional Keyboard with built-in smart card reader

Low profile key design with tactile feeling

Full 104/105 key design, support US and EU layout

Support firmware upgrade

Durable legends printed with UV coating

Sealed membrane to increase the membrane circuit life

Smart Card Reader Spec

Access to all ISO-7816 and EMV CPU cards (T=0, T-1) through PC/SC drivers
Communication Speed with the smart card: up to 826Kbps (when supported by the SC)
Synchronous cards through a comprehensive API
5V/55mA, 3V/50mA, 1.8V/20mA smart card power supply
Full ISO7816 and EMV2000 compliances
Use high quality landing contact type smart card connector
Short circuit protection
Card removal detection when powered on
ESD protection on card los: 8KV contact
Drivers support: PC/SC, CT/API, CCID, Synchronous API

Technical Data

[Electronics]


Power supply: +5V/DC +/-10%
Current input: <100mA
Interface: USB2.0 (USB-A), Full Speed
LED indicators: Cap / Num / Scroll / IC Card

[Mechanical]

Number of keys:
- 104: US ANSI layout
- 105: European ISO layout
Individual key life cycle: 10 million key strokes
Key switch technology: rubber dome over sealed membrane
Key actuation force: 65g +/- 10g
Key travel: 3 +/- 0.5mm
Smart Card Connector Life: 500,000 insertions

[Others]

Storage temperature: -40°C to +55°C
Operating temperature: 0°C to +45°C
Operating humidity: 40% to 90%
Dimensions: 472 x 183 x 47.5 mm
Certificate/ Compliance: FCC, CE / RoHS



HENGYU

Heng Yu Technology (HK) Limited
<http://www.hengyu-tech.com>