

K104S

FENGYU



Professional Keyboard

K104S

FENGYU

Key Features

Standard 104/105 full size keyboard layout, with built-in magstripe and smart card reader

All keys are made from Cherry MX key switches, good tactile feelings

Magstripe reader settings are programmable by Matrix Maker

Smart card reader complies with ISO-7816, support PC/SC and CCID

With internal strong metal plate to enhance the protection against ESD is increased

Key legends: Laser-engraved or high quality silk screen printed with UV coating, durable screen printed keycap symbols

Available in USB and PS/2 interface

MagStripe Reader Features

MagStripe header, tailer, track sequence, encoding are programmable

Comply with ISO 7812, IBM standards, AAMVA, JIS-2

Support multi-country code settings

Support programmable MSR setting for the header, tailor, separator, suffix and prefix, track sequence

Track 1: 210BPI with max 76 characters

Track 2: 210BPI with max 107 characters or 75BPI with max 37 characters

Track 3: 210BPI with max 107 characters

Card swipe speed: 10 to 100 cm/s; Speed:3-125 ips at 75 BPI; 3-50 ips at 210 BPI

500,000 swipe cycles

Smart Card Reader Spec

Access to all ISO-7816 and EMV CPU cards (T=0, T-1) through PC/SC drivers

Communication Speed with the smart card: up to 826Kbps (when supported by the SC)

Synchronous cards through a comprehensive API

5V/55mA, 3V/50mA, 1.8V/20mA smart card power supply

Full ISO7816 and EMV2000 compliances

Use high quality landing contact type smart card connector

Short circuit protection

Card removal detection when powered on

ESD protection on card Ios: 8KV contact

Drivers support: PC/SC, CT/API, CCID, Synchronous API

Professional Keyboard

Technical Data

[Electronics]

Power supply

PS/2: +5V/DC $\pm 10\%$

USB: +5V/DC $\pm 5\%$

Current input

PS/2: <100mA

USB: <100mA

[Mechanical]

Total travel: 4 – 0.4mm

Pre-travel: 2 ± 0.6 mm

Peak load before make: 60 ± 20 cN

Individual key life cycle: 50 million key strokes

Card swipe speed: 10 to 100 cm/s; Speed: 3-125 ips at 75 BPI; 3-50 ips at 210 BPI

Magnetic head life: 500,000 swipe cycles

Smart Card Connector Life: 500,000 insertions

[Others]

Storage temperature: -40°C to +55°C


Operating temperature: 0°C to +40°C

Operating humidity: 40% to 90%

Dimensions:

Gift box:

Certificates: FCC/CE



HENGYU

Heng Yu Technology (HK) Limited
<http://www.hengyu-tech.com>