

# KDS-121D

## 厨房系统一体机

FENGYU



# KDS-121D

## 厨房系统一体机


FENGYU

## 主要特点

- 专业厨房12.1" 一体机, 加固型设计
- 配置钢化玻璃制成的坚固触摸屏
- 无风扇系统, 采用坚固的金属外壳 高品质电子工业组件, 绝对可靠
- 带母连接器插头的密封电缆线 SR 设计, 可轻松延长电缆线 长度
- 支持多种 Intel CPU 平台, Celeron、i3-Core 和 i5-Core
- 清晰明亮的触摸屏, 操作直观。即使手指湿润或戴乳胶手套也能发挥全部功能
- 100 % 耐水和油脂蒸汽以及食品酸
- 100% 卫生, 光滑的表面和无边设计
- 可选配恒宇的自家厨房系统软件

# KDS-121D

## 技术规范



| Features      | Model                      | KDS-121D-S64  | KDS-121D-SI3   | KDS-121D-SI5           |
|---------------|----------------------------|---|--|------------------------|
| Processor     | CPU                        | Intel® Celeron® Processor J6412                         | Intel® i3-1115G4                                       | Intel® i5-1135G7       |
|               | Frequency                  | Up to 2.6GHz  | Up to 4.1GHz   | Up to 4.2GHz           |
| Memory        | Technology                 | Support DDR4 3200MHz, 1*non-ECC SO-DIMM Slot            |  |                        |
|               | Max. Capacity              | Up to 32GB  |  |                        |
| Display       | Controller                 | Intel HD Graphics                                       | Intel UHD Graphics                                     | Intel Iris Xe Graphics |
|               | Graphic Memory             | Shared System Memory up to 1.7GB SDRAM                  |  |                        |
|               | Main Display Resolution    | 12.1" (800 x 600), ratio 4:3                            |  |                        |
|               | Active Area                | 246 x 184.5(mm)   |  |                        |
|               | Luminance                  | 450cd/m2  |  |                        |
|               | Viewing Angle (R/ L/ U/ B) | 80/ 80/ 65/ 75  |  |                        |
|               | Touch Panel                | PCAP, USB protocol                                      |  |                        |
| Ethernet      | Controller                 | Realtek GBE LAN Chip (RJ45, 10/100/1000 Mbps)           |  |                        |
| Storage       | Primary                    | M.2 (NGFF) Key-B/B+M Slot<br>(SATA SSD, 2242/2260/2280) | M.2 (NGFF) Key-M Slot<br>(PCIe x4 NVMe SSD, 2242/2280) |                        |
|               |                            |   |  |                        |
| I/O Interface | Main USB                   | 2 x USB-A 2.0   |  |                        |
|               | Audio                      | Line-Out 3.5mm Jack                                     |  |                        |
|               | Serial                     | 1 x DB9 COM   |  |                        |
|               | LAN                        | RJ45 / POE++ LAN (Optional)                             |  |                        |
| Options       | Bumpbar                    | BB20A / MK15F / USB Speaker                             |  |                        |
| Power Adaptor | Input                      | Universal AC 100~240V, 50/60 Hz                         |  |                        |
|               | Output                     | DC +12V 5A  | DC +12V 7A   |                        |
| Environment   | Storage Temperature        | -15°C ~ 55°C  |  |                        |
|               | Operation Temperature      | -0°C ~ 40°C   |  |                        |
|               | Operation Humidity         | 10% ~ 85%   |  |                        |
| Mounting      | Standard                   | VESA Mount 100 x 100(mm)                                |  |                        |
| Dimension     | Panel (w/o stand)          | 252 x 177 x 44(mm)                                      |  |                        |

- Heng Yu Technology (HK) Limited
- <http://www.hengyu-tech.com>