

KDS-156AP

Kitchen Display Terminal



KDS-156AP

Kitchen Display Terminal

FENGYU

Main Features

- 15.6" AIO terminals designed for kitchen and other rugged environment
- Robust display made of tempered glass
- Fanless system in a robust metal housing. High-quality electronics industrial components for absolute reliability
- Sealed cable SR design with female connector plugs allows easy extension of the cable length.
- Support several Intel CPU platforms, Celeron, i3-Core and i5-Core
- Clear and bright touch display, intuitive to operate. Full functionality even with wet fingers or latex gloves
- 100 % resistant to water and grease vapor as well as food acids.
- 100 % hygienic thanks to smooth surfaces and edgeless design.
- Can come with optional Heng Yu Kitchen Display software
- Can be equipped with Heng Yu bumpbars

KDS-156AP Technical Specification



Features	Model	KDS-156AP-S64	KDS-156AP-SI3	KDS-156AP-SI5
Processor	CPU	Intel® Celeron® Processor J6412	Intel® i3-1115G4	Intel® i5-1135G7
	Frequency	Up to 2.6GHz	Up to 4.1GHz	Up to 4.2GHz
Memory	Technology	Support DDR4 3200MHz, 1*non-ECC SO-DIMM Slot		
	Max. Capacity	Up to 32GB	Up to 64GB	
Display	Controller	Intel HD Graphics	Intel UHD Graphics	Intel Iris Xe Graphics
	Graphic Memory	Shared System Memory up to 1.7GB SDRAM		
	Main Display Resolution	15.6" (1366 x 768), ratio 16:9		
	Active Area		344.232 x 193.536(mm)	
	Luminance		220cd/m2	
	Viewing Angle (R/ L/ U/ B)		45/ 45/ 20/ 40	
	Touch Panel	PCAP, USB protocol		
Ethernet	Controller	Realtek GBE LAN Chip (RJ45, 10/100/1000 Mbps)		
Storage	Primary	M.2 (NGFF) Key M Slot (NVME SSD, 2280)	M.2 (NGFF) PCIe4 Key M Slot (NVME SSD, 2280)	
I/O Interface	Main USB	2 x USB-A 3.0, 2 x USB-A 2.0		
	Audio	Line-Out/ Mic 3.5mm Jack		
	Serial	DB9 x 1 (Optional)		
	LAN	RJ45 / POE+ LAN (Optional)		
Options	Bumpbar	BB20A / MK15F		
Power Adaptor	Input	Universal AC 100~240V, 50/60 Hz		
	Output	DC +12V 5A/ Support POE++ power (Optional)	DC +12V 7A/ Support POE++ power (Optional)	
Environment	Storage Temperature	-15°C ~ 55°C		
	Operation Temperature	-0°C ~ 40°C		
	Operation Humidity	10% ~ 85%		
Mounting	Standard	VESA Mount 100 x 100(mm)		
Dimension	Panel (w/o stand)	380 x 239 x 53(mm)		

- Heng Yu Technology (HK) Limited
- <http://www.hengyu-tech.com>